

World Intellectual Property
Organization
International Bureau



PCT

(10) International Publication Number
WO 2004/089105 A1

3) International Publication Date
21 October 2004 (21.10.2004)

International Patent Classification:
A23G 9/14

International Filing Date: **30 March 2004 (30.03.2004)**

International Application Number:
PCT/DK2004/000220

(25) Filing Language:
English

(26) Publication Language:
English

(30) Priority Data:
PA 2003 00531

(71) Applicant (for all designated States except US): **TETRA
LAVAL HOLDING & FINANCE S.A. [CH/CH]; Avenue
Général-Guisan 70, CH-1009 Pully (CH).**

(72) Inventor; and
(75) Inventor/Applicant (for US only): **HANSEN, Per,
Henrik [DK/DK]; Mallinggardsvej 69, DK-8340 Malling
(DK).**

(74) Agent: **PATENTGRUPPEN APS; Aosgaaarden, Aaboule-
varden 31, DK-8000 Aarhus C (DK).**

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, GR, GU, HT, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MY, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: **A METHOD AND AN APPARATUS FOR PRODUCING ICE CONFECTION**



(57) Abstract: The present invention concerns an apparatus and a method for producing ice confection comprising mould cavities arranged on lamellae disposed in an endless belt along which are arranged process means for the production of the ice confection by conveying the lamellae between the process means, wherein the apparatus comprises an uneven number of lamellae and the process means are arranged along the belt in such a way, that the ice confection production process may be completed by two full circulations of one lamella on the belt. Due to the uneven number of lamellae a specific lamella will change stop position for each circulation. Hereby, a number of advantages are obtained through an optimal utilization of the lower lamella sequence, such that the shortest possible apparatus is obtained.

1/PRK
1005 Rec'd PCT/PTO 07 OCT 2005

A METHOD AND AN APPARATUS FOR PRODUCING ICE CONFECTION

10/552523

The present invention relates to a method and an apparatus for producing ice confection, i.e. ice cream products with a core of ice cream enclosed in a cover,
5 preferably a chocolate shell.

Production of ice confection is in general performed in two ways. According to a first production method the production is performed by extrusion of the ice mass, which is cut into portions with subsequent freezing in cold air. Afterwards, the
10 portion is transferred to a chocolate covering device and then on via a chocolate cooling belt to wrapping and storage. The disadvantage of such a production method is the long freezing requiring around twenty minutes for solidifying the ice mass. Further, the chocolate cover evens out the contours of the shape of the ice cream product, a disadvantage also being that the heat supplied to the ice mass by the
15 chocolate melts part of the ice mass, and thus the quality of the ice product is impaired.

According to another production method the ice confection is moulded in mould cavities. First, a chocolate shell is manufactured by filling in chocolate and emptying
20 surplus chocolate from the mould cavities. Then, partly liquid ice cream is filled into the chocolate shells and a final layer of chocolate is applied after freezing the ice cream in cold air, which layer melts together with the abovementioned chocolate shell. The machine comprises a number of lamellae, which are connected together in an endless belt. Each lamella is provided with a row of cavities or detachable
25 moulds, corresponding to the top and sides of the product. The lamellae are conveyed stepwise by using two chains being moved by means of chain wheels at each end of the belt run. By this machine the following sub-processes are performed successively:

- Pre-cooling the empty moulds in a compartment with cold air;
- 30 • Filling chocolate into the cavities;
- Suction of surplus chocolate after part of the chocolate has solidified;

- Scraping off chocolate spilled on the top face of the moulds;
- Cooling the chocolate shell with cold air;
- Filling and levelling ice cream into the chocolate shell;
- Cooling the ice cream;
- 5 • Filling chocolate on the top face of the ice cream;
- Removing surplus chocolate;
- Scraping off chocolate spilled on the mould plane;
- Cooling the chocolate in cold air; and
- Extracting the products for wrapping.

10

Using standard ice cream at a temperature of around -4 to -8°C a cooling takes place in cold air for cooling the ice cream another approx. 10°C, which takes very a long time, though partly remedied by the fact that the cooling zone is designed very long. There are several drawbacks to this type of machine, as the emptying out and the

15 scraping off occur with the cavities facing upwards. Further, all the processes are performed on the upper sequence of the endless belt (the upper lamellae loop), whereby the entire lower part of the belt is not utilised. This renders the machine very long. However, one design is known in which the mould cavities of the lower part are facing downwards during emptying of surplus chocolate from the top face of

20 the ice cream and during scraping off chocolate from the mould plane. The drawback being the first emptying out and scraping off still occurs with the cavities facing upwards, and the machine is consequently still rendered relatively long.

It is therefore an object of the present invention to provide a faster and better suited

25 production of ice confection in an apparatus which does not take up a large amount of space.

An apparatus and a method for producing ice confection comprises mould cavities arranged on lamellae disposed in an endless belt along which are arranged process

30 means for the production of the ice confection by conveying the lamellae between the process means, wherein the apparatus comprising an uneven number of lamellae

and the process means are arranged along the belt in such a way, that the ice confection production process may be completed by two full revolutions of a lamella on the belt.

- 5 Due to the uneven number of lamellae, a given lamella will change stop position for each circulation. Hereby, a number of advantages are obtained through an optimal utilization of the lower lamella sequence, such that the shortest possible apparatus is obtained.
- 10 By an apparatus according to the invention it is only necessary having one cooling zone, as one common freeze compartment may be provided, while the lamella during one production cycle is moved four times through the compartment, two times in the upper and two times in the lower belt sequence, respectively.
- 15 The two chocolate fillings may be performed in the same area and e.g. may be using one common process means. Additionally, the two processes of chocolate emptying and scraping off the moulds are performed with the mould cavities, i.e. the lamellae facing downwards. Thus, it is possible to provide the apparatus with a drain for a shared accumulation for these process steps.
- 20 The freezing period for the ice cream and accordingly the size of the freeze compartment may be reduced significantly by the application of a low temperature ice cream, preferably having a temperature from approx. -8 to -15°C for filling. Said low temperature allows also for the products, after wrapping on subsequent process
- 25 means, may be taken directly to a freezer storage. The freezing period may also be reduced by cooling the mould cavities of the lamellae with liquid nitrogen, which is applied to the mould cavities for pre-cooling prior to filling of chocolate in the moulds for the production of the chocolate shell. Also, the nitrogen gas produced by this cooling will contribute to the cooling of the production facility in general.

As a substitute for stepwise conveying two lamellae at a time, the conveying of the belt may be continuous at an even speed. Thus the same advantages may be gained, as long as the number of lamellae is uneven and the processes occurs at the predetermined stationary positions relative to the belt and having a process cycle
5 corresponding to every second lamellae.

In the following the invention is described in detail referring to the supplied drawings, in which:

- 10 Fig. 1a and 1b shows a lamella with mould cavities for moulding ice products;
Fig. 2 and 3 shows two embodiments of the production process known in the art; and
Fig. 4 is a schematic illustration of an apparatus for production of ice
confection according to the invention.

15

In Fig. 1a and 1b are shown a lamella 50 with a number of mould cavities 30 formed or mounted in the lamella 50. Each side of the lamella 50 is connected to a chain 20. The chains 20 surround two rolls or wheel 60 in such a way that the lamellae are disposed in a belt sequence 40, as shown in the following figures. The chains and the
20 lamellae thus together form an endless belt. The lamellae 50 are consequently rotated in a belt sequence 40.

The production of the ice confection products is performed by moulding in mould cavities 30. Firstly, a chocolate shell is produced by filling in chocolate and emptying
25 surplus chocolate from the mould cavities. Then, partly liquid ice cream is filled into the chocolate shells and after freezing in cold air a final layer of chocolate is applied, which melts together with the above mentioned chocolate shell.

In figs. 2 to 4 are shown a number of lamellae connected together in an endless belt.
30 Each lamella is provided with a row of cavities or detachable moulds, corresponding to the top and sides of the product. The lamellae are conveyed stepwise by the two

chains being moved by means of chain wheels in each end of the belt run. By this production method for producing ice confection the apparatus performs the following sub-processes successively:

- 1) pre-cooling of the empty moulds in a compartment with cold air;
- 5 2) filling of chocolate in the cavities;
- 3) suction of surplus chocolate after a part of the chocolate has solidified;
- 4) scraping off chocolate spilled on the top surface of the moulds;
- 5) cooling the chocolate shell with cold air;
- 6) filling and levelling ice cream in the chocolate shell;
- 10 7) cooling the ice cream;
- 8) filling chocolate on the top face of the ice cream;
- 9) removing surplus chocolate;
- 10) scraping off chocolate spilled on the mould plane;
- 11) cooling the chocolate in cold air; and
- 15 12) extraction of the products for wrapping.

The sub-processes takes place along the belt and the position for the individual sub-processes are shown in fig. 2 to 4 using the above reference numbers.

- 20 Using usual ice cream having a temperature of approx. -4 to -8°C , the cooling takes place in cold air in order to lower the ice cream temperature by another approx. 10°C , which will take a long time, though partly remedied by the fact that the cooling zone is designed very long according to the known art, as shown in fig. 2. There are several drawbacks to his type of machine, as the extraction 3, 9 and the
- 25 scraping off 4, 10 occur with the cavities facing upwards. Further, every single process is performed on the upper sequence of the endless belt (the upper lamellae loop), whereby the entire lower part of the belt is not utilised.

- According to another design, see fig. 3, a machine is known in which the mould
- 30 cavities in lower part have the openings face downwards for emptying 9 and scraping off 10 chocolate from the mould plane. The drawbacks are the first chocolate empty-

ing 3 and scraping off 4 still occurs with the cavities facing upwards, and the machine is consequently still rendered relatively long.

An apparatus according to the invention for producing ice confection is shown in fig. 4. This design renders the belt 40 and accordingly the entire apparatus significantly shorter, since the process steps are arranged both above and below the lamellae of the belt and since each lamella 50 has to circulate to entire sequences in connection with the production of the ice confection products in it. Due to the uneven number of lamellae a specific lamella will change stop position for each circulation. The belt is, for each process cycle, preferably conveyed stepwise two lamellae at a time. Accordingly, the process means may be arranged such that all freezing processes 1, 7; 5, 11 may be gathered in one common freeze compartment. The two filling processes 2, 8 are arranged in the same area and may possibly be performed by the same process means, if the conditions allow it. The two processes of emptying out the chocolate 3, 9 occur in the beginning of the lower sequence, followed by the corresponding scraping off 4, 10 chocolate of the moulds. Since the mould cavities are facing downwards during emptying out and scraping off one common collection means may be provided, such as a collection tray for these processes. An optimal utilization of the lower lamella sequence is obtained, which provides the shortest possible machine.

25

30

CLAIMS

- 5 1. An apparatus for producing ice confection comprising mould cavities arranged on lamellae disposed in an endless belt along which are arranged process means for the production of the ice confection by conveying the lamellae between the process means,
characterized in that
- 10 the apparatus comprises an uneven number of rows of mould cavities, such as lamellae, and the process means are arranged along the belt in such a way, that the ice confection production process may be completed by two full revolutions of a specific mould cavity on the belt.
- 15 2. An apparatus according to claim 1, wherein there is provided one common process means for pre-cooling the empty moulds, cooling of the chocolate shell, cooling of the ice cream and cooling of chocolate, said process means comprising a cooling zone preferably extending over at least an area corresponding to two lamellae on the belt in both the upper and lower sequence.
- 20 3. An apparatus according to claim 1 or 2, wherein process means for the chocolate filling into the cavities and chocolate filling on the top face of the ice cream are arranged in the same area along the upper belt sequence.
- 25 4. An apparatus according to any of the claims 1 to 3, wherein process means for the removal, e.g. for emptying the surplus chocolate after a part of the chocolate has solidified to a shell and removing surplus chocolate on the top face of the ice cream are arranged in the same area along the lower belt sequence.

5. An apparatus according to any of the claims 1 to 3, wherein the lamellae in the belt, for each process cycle, are conveyed stepwise two lamellae or rows of mould cavities at a time.

5 6. An apparatus according to any of the claims 1 to 4, wherein the lamellae in the belt, for each process cycle, are conveyed continuously two lamellae or rows of mould cavities at a time.

7. An apparatus according to any of the preceding claims, wherein process means for
10 pre-cooling of the mould cavities by means of liquid nitrogen are arranged.

8. A method for producing a covered ice cream product, particularly a chocolate covered ice cream product such as ice confection, comprising production of a cover shell in mould cavities on a lamella, filling of said shell with ice cream, which after
15 freezing is applied a cover layer melting together with the cover shell, said method being completed by the movement of a number of lamellae arranged in an endless belt, whereby the individual lamella is moved between process means disposed along said belt,

characterized in that

20 the belt comprises an uneven number of rows of mould cavities, such as lamellae, and the production process of the ice confection in the mould cavities in a lamella is completed by two full circulations of a specific mould cavity, the belt being conveyed stepwise two lamellae at a time or continuously at an even speed, whereby two rows of mould cavities are conveyed for each function cycle of the production
25 processes.

9. A method according to claim 8, wherein application of a low temperature ice cream, preferably having a temperature from approx. -8 to -15°C for filling of the ice cream is utilised.







FIG. 2 PRIOR ART



PRIOR ART



INTERNATIONAL SEARCH REPORT

International Application No

PCT/DK2004/000220

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A23G9/14 A23G9/04 A23G9/22 A23G9/24

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A23G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 819 449 A (CURTI CARLO ET AL) 11 April 1989 (1989-04-11)	1-7
Y	the whole document	8,9
X	EP 1 249 175 A (SIDAM SRL) 16 October 2002 (2002-10-16)	1-7
Y	the whole document	8,9
X	US 4 530 214 A (ELLSWORTH CARROLL V ET AL) 23 July 1985 (1985-07-23)	1-7
A	the whole document	8,9
A	WO 98/00030 A (TETRA PAK HOYER A S ; WALDSTROEM EJVIND (DK)) 8 January 1998 (1998-01-08)	1-9
	the whole document	
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *Z* document member of the same patent family

Date of the actual completion of the international search

5 July 2004

Date of mailing of the international search report

12/07/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Boddaert, P

INTERNATIONAL SEARCH REPORT

International Application No

PCT/DK2004/000220

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 907 472 A (LUTSEY THOMAS H) 23 September 1975 (1975-09-23) the whole document -----	1-9
A	US 4 576 562 A (ANDERSON DAVID N) 18 March 1986 (1986-03-18) the whole document -----	1-9
A	GB 1 260 536 A (FMC) 19 January 1972 (1972-01-19) the whole document -----	1-9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/DK2004/000220

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4819449	A	11-04-1989	NONE	
EP 1249175	A	16-10-2002	IT EP US	MI20010738 A1 1249175 A2 2002146488 A1
				07-10-2002 16-10-2002 10-10-2002
US 4530214	A	23-07-1985	AU AU BR CA DK EP ES FI JP NO NZ	578670 B2 4048885 A 8501604 A 1252638 A1 149385 A 0158894 A2 8608813 A1 851278 A 60256351 A 851297 A , B, 211609 A
				03-11-1988 10-10-1985 03-12-1985 18-04-1989 05-10-1985 23-10-1985 16-12-1986 05-10-1985 18-12-1985 07-10-1985 11-07-1986
WO 9800030	A	08-01-1998	DK AU AU CA CA DE DE DE DE WO WO DK DK EP EP US US	70896 A 3254297 A 3254797 A 2258922 A1 2259244 A1 69715252 D1 69715252 T2 69716441 D1 69716441 T2 9800030 A1 9800031 A1 920260 T3 955816 T3 0920260 A1 0955816 A1 6092388 A 6156366 A
				29-12-1997 21-01-1998 21-01-1998 08-01-1998 08-01-1998 10-10-2002 18-09-2003 21-11-2002 18-06-2003 08-01-1998 08-01-1998 20-01-2003 09-12-2002 09-06-1999 17-11-1999 25-07-2000 05-12-2000
US 3907472	A	23-09-1975	CA	1013204 A1
				05-07-1977
US 4576562	A	18-03-1986	CA DE DK EP JP JP JP KR	1232792 A1 3583815 D1 187585 A 0159632 A2 1857003 C 5052171 B 60234550 A 9209466 B1
				16-02-1988 26-09-1991 28-10-1985 30-10-1985 07-07-1994 04-08-1993 21-11-1985 17-10-1992
GB 1260536	A	19-01-1972	BE DE FR NL US	732608 A 1921663 A1 2007928 A5 6906882 A 3488976 A
				16-10-1969 20-11-1969 16-01-1970 10-11-1969 13-01-1970